



## CALCITE SPEC SHEET

WHOLE-HOME pH CORRECTION

# Calcite Neutralizer

Acidic water · natural calcite ·  
automatic backwash

### AT A GLANCE

|          |                      |
|----------|----------------------|
| System   | pH neutralizer       |
| Tank     | 12" × 52"            |
| Media    | Natural calcite      |
| Inlet pH | 5.0 – 7.0            |
| Flow     | Up to 28 GPM         |
| Warranty | Lifetime tank & disc |

Treats acidic water as it enters your home. Natural calcium carbonate slowly dissolves to raise pH toward a less-corrosive balance, helping protect copper plumbing, fixtures and water-using appliances. Runs on a BluePeak ProValve with automatic backwashing to keep the mineral bed loose and flowing.

No chemical injection

NSF/ANSI 61 components

Assembled in Texas

Lifetime tank warranty

### KEY SPECIFICATIONS

|                      |                                                       |
|----------------------|-------------------------------------------------------|
| Type                 | pH neutralizer (does not soften or filter chlorine)   |
| Media                | Natural calcite — crushed, screened calcium carbonate |
| Media tank (D × H)   | 12" × 52"                                             |
| Recommended inlet pH | 5.0 – 7.0                                             |
| Valve flow rate      | Up to 28 GPM                                          |
| Control valve        | BluePeak ProValve — ceramic disc                      |
| Connection size      | 1"                                                    |
| Bypass valve         | 1" full-flow, included                                |
| Backwash             | Automatic, demand-initiated                           |
| Best suited to       | Well water with low pH (acidic), blue-green staining  |

### OPERATING REQUIREMENTS

|                     |                                                          |
|---------------------|----------------------------------------------------------|
| Operating pressure  | 30 – 125 PSI                                             |
| Water temperature   | 40° – 110°F (4° – 43°C)                                  |
| Electrical          | 120V / 60Hz — 12V transformer                            |
| Media replenishment | Calcite is consumed as it works — topped up periodically |

### WORTH BEING CLEAR ABOUT

- Raises pH of acidic water
- Reduces pipe corrosion & metal leaching
- Helps stop blue-green staining
- Adds calcium — hardness may rise
- A softener is often recommended downstream
- Does NOT remove iron, sulfur or chlorine

### COMPONENTS, SOURCING & WARRANTY

|                |                                                                                              |
|----------------|----------------------------------------------------------------------------------------------|
| Control valve  | BluePeak ProValve — Hanksraft ceramic disc, assembled in Wisconsin, 72-hour memory backup    |
| Mineral tank   | Enpress fiberglass pressure tank — made in Ohio · NSF-certified polishing gravel support bed |
| Assembly       | Fort Worth, Texas                                                                            |
| Certifications | Tank, valve and support gravel certified to NSF/ANSI 61                                      |
| Warranty       | Lifetime — tank & ceramic disc · 5 years — valve body & board · 1 year — labor               |
| Installation   | Included — by a licensed North Carolina plumber                                              |
| Drinking water | Free reverse osmosis drinking system included, installed at the kitchen sink                 |

### BluePeak Water Filtration

(984) 401-8890 · [clean@bluepeakwaterfiltration.com](mailto:clean@bluepeakwaterfiltration.com) · [bluepeakwaterfiltration.com](http://bluepeakwaterfiltration.com) · Serving the Triangle and surrounding counties  
BluePeak Home Solutions Group LLC, DBA BluePeak Water Filtration